

BioPure PTFE gaskets

polytetrafluoroethylene

FEATURES AND BENEFITS


- Solid PTFE for ultimate chemical resistance and purity
- Precision engineered to achieve a smooth bore, contamination free fluid path under clamping compression
- Manufactured in accordance with ASME-BPE standards
- USP Class VI compliant and ADCF
- Compliant with FDA regulations CFR 21 177.2600
- Full material lot traceability




TECHNICAL DATA

Specifications	
Temperature resistance	-212C to 232C (-350F to 450F continuous)

ORDER INFORMATION



Unflanged type gasket for sizes $< 3/4''$ flange OD



Unflanged type gasket for sizes $> 3/4''$ flange OD

Part number	Size inch	I.D ($\varnothing B$) inch(mm)	O.D ($\varnothing A$) inch(mm)	Quantity
42MPG-050-25	1/2	0.38 (9.7)	0.85 (21.6)	25
42MPG-075-25	3/4	0.62 (15.7)	0.85 (21.6)	25
40MPG-100-25	1	0.88 (22.4)	1.98 (50.3)	25
40MPG-150-25	1 1/2	1.38 (35.1)	1.98 (50.3)	25
40MPG-200-25	2	1.88 (47.8)	2.52 (64.0)	25
40MPG-250-25	2 1/2	2.38 (60.5)	3.05 (77.5)	25
40MPG-300-25	3	2.88 (73.2)	3.58 (90.9)	25
40MPG-400-25	4	3.84 (97.5)	4.68 (118.9)	25
40MOG-600-25	6	5.84 (148.3)	6.57 (166.9)	25

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the users responsibility to ensure product suitability for use within their application. Watson-Marlow and pureu are registered trademarks of Watson-Marlow Limited. Bio Y, BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve and BioTube applicator are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. Q-Clamp is used under licence.



wmftg.com
info@wmftg.com
+44 (0) 2392 499000